



RIGHT SIDE VIEW

REAR VIEW

| BOILER SPECIFICATION CHART | |
|-----------------------------------|----------------------------------|
| BUILT TO ASME CODE SECTION I FOR: | 150 PSI |
| HEATING SURFACE | 150 SQ. FT. |
| FURNACE OUTSIDE DIA. | 14 INCHES |
| FURN. VOL. | (FURN. & TURNAROUND) 6.6 CU. FT. |
| WATER CAPACITY (OPERATING) | 215 GALS. |
| WATER CAPACITY (FLOODED) | 252 GALS. |
| SHIPPING WEIGHT | 3500 LBS. |

| REASON FOR CHANGE | |
|-------------------|------------|
| R BY: | DATE: (MM) |

THIS DRAWING IS THE PROPERTY OF HURST BOILER AND WELDING CO., INC. AND MAY NOT BE COPIED OR REPRODUCED IN ANY WAY UNLESS AUTHORIZED IN WRITING BY HURST BOILER AND WELDING CO., INC. AND MUST BE RETURNED UPON REQUEST.

HURST BOILER & WELDING CO., INC.
 P.O. BOX 38, HIGHWAY 319, COOLIDGE, GA. 31738
 PHONE: 228-346-3443 FAX: 228-346-3874

SERIES 500 - 4 PASS WETBACK SCOTCH BOILER
30 HP - 150 PSI STEAM

| | | | | |
|--------|----------|---------|-------------|--------------|
| SCALE: | DNW. BY: | DATE: | CHK'D. BY: | DRAWING NO.: |
| NTS 24 | REW | 3/15/02 | DNW 4/17/02 | SF--30-150 |