



DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE.
CONSULT FACTORY FOR CERTIFIED DRAWINGS.

CAPACITIES-OUTPUT	
HORSEPOWER	— 25
LBS./HR. STEAM	— 863
KG./HR. STEAM	— 391
BTU/HR. X 1000	— 837
KCAL/HR. X 1000	— 211
INPUT REQUIRED	
BTU/HR. X 1000	— 1046
KCAL/HR. X 1000	— 264
CONNECTION SIZES	
A	1 1/4" STEAM OUTLET
B	1" SPARE
C	1 1/2" INSPECTION
D	1" FOR PROBE TYPE 2nd
E	LOW WATER CUT-OFF
F	SAFETY VALVE, 1" OUTLET (1" CPLG.)
F	1" BLOWDOWN VALVE
G	3/4" FEEDWATER LINE
H	WATER CAP. AT NWL — 54 GAL.
I	WATER CAP. FLOODED — 79 GAL.
J	SHIPPING WEIGHT — 2950 LBS.

HURST BOILER & WELDING CO., INC.

P.O. DRAWER 529, HIGHWAY 319 S., COOLIDGE, GA. 31738
PHONE: 912-346-3545 FAX: 912-346-3874

25 HP-4 PASS VERTICAL TUBELESS BOILER WITH 30 GAL. BOILER FEEDWATER SYSTEM & 8" DIA. X 26" BLOWDOWN SEPARATOR
150 PSI DESIGN PRESSURE

R	BY:	DATE:	CHK'D:	REASON FOR CHANGE

SCALE:	DMN. BY:	DATE:	CHK'D. BY:	DRAWING NO.:
NTS 24	MB	10-26-99	JHO	447-25-150RB

THIS DRAWING IS THE PROPERTY OF HURST BOILER AND WELDING CO., INC. AND MAY NOT BE COPIED OR REPRODUCED IN ANY WAY UNLESS AUTHORIZED IN WRITING BY HURST BOILER AND WELDING CO., INC. AND MUST BE RETURNED UPON REQUEST.