



4 1/2" DIA. 0-300
PSI PRESS. GAUGE

PUMP CONTROL, WITH
LOW WATER CUT-OFF
AND GAUGE GLASS

CAPACITIES-OUTPUT	
HORSEPOWER	— 10
LBS./HR. STEAM	— 345
KG./HR. STEAM	— 156
BTU/HR. X 1000	— 335
KCAL/HR. X 1000	— 84
INPUT REQUIRED	
BTU/HR. X 1000	— 418
KCAL/HR. X 1000	— 105
CONNECTION SIZES	
A	1" STEAM OUTLET
B	1" SPARE
C	1 1/2" INSPECTION
D	1" FOR PROBE TYPE 2nd
LOW WATER CUT-OFF	
E	SAFETY VALVE, 1" OUTLET (1" PLG.)
F	1" BLOWDOWN VALVE
G	3/4" FEEDWATER LINE
H	WATER CAP AT NWL-48 GAL.
I	WATER CAP AT FLOODED-62 GAL.
J	SHIPPING WEIGHT 1700 LBS.

DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE.
CONSULT FACTORY FOR CERTIFIED DRAWINGS.

LEFT SIDE VIEW

FRONT VIEW

R	BY:	DATE:	CHK'D:	REASON FOR CHANGE
NTS 24	JHO	11/14/01	RBC	

HURST BOILER & WELDING CO., INC.
10 HP-4 PASS VERTICAL TUBELESS BOILER
150 PSI DESIGN PRESSURE

SCALE:	DMN. BY:	DATE:	CHK'D. BY:	DRAWING NO.:
NTS 24	JHO	11/14/01	RBC	4PT-10-150

THIS DRAWING IS THE PROPERTY OF HURST BOILER AND WELDING CO., INC. AND MAY NOT BE COPIED OR REPRODUCED IN ANY WAY UNLESS AUTHORIZED IN WRITING BY HURST BOILER AND WELDING CO., INC. AND MUST BE RETURNED UPON REQUEST