



Tanks are available in Carbon Steel and Stainless Steel

### SPECIFICATIONS

(ALL DIMENSIONS ARE IN INCHES)

DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE, CERTIFIED DRAWINGS AVAILABLE UPON REQUEST

BOILER HP	TANK CAPACITY (GAL.)	(A) LENGTH	(B) WIDTH	* (C) HEIGHT 15-150 PSI	* (C) HEIGHT 200-250 PSI	* (C) HEIGHT 300 PSI	** (D) WATER SUPPLY	(E) COND. RETURN	(F) VENT	(G) OVER FLOW	(H) DRAIN	SHIPPING WIEGHT 150 PSI
15-30	30	30	19	60	68	69	1/2	2	2	1 1/2	3/4	550
40-60	60	36	25	67	73	86	1/2	2	1 1/2	1 1/4	3/4	650
70-80	80	46	29	67	75	86	1/2	2	1 1/2	1 1/4	3/4	700
100	100	48	26	74	76	87	3/4	2	1 1/2	1 1/4	3/4	825
125-150	150	48	31	79	90	93	3/4	2	1 1/2	2	1	1100
200	200	60	34	88	93	96	3/4	2 1/2	1 1/2	2	1	1250
250	250	72	35	89	93	96	3/4	2 1/2	1 1/2	2	1	1400
300	300	72	38	92	96	99	3/4	2 1/2	2	2	1	1730
350	350	84	38	92	96	99	3/4	2 1/2	2 1/2	2	1	1835
400	400	72	44	98	102	114	3/4	3	2 1/2	2	1 1/4	2050
500	500	84	44	104	110	114	3/4	3	2 1/2	2	1 1/4	2300
600	600	84	48	108	114	118	3/4	3	2 1/2	2	1 1/4	2450
700-800	800	114	48	120	118	125	3/4	3	2 1/2	2	1 1/4	2940
900-1000	1000	96	58	130	135	135	(2) 3/4	3	3	3	1 1/2	4200

\* Overall height may change, depending on NPSH requirements of the pumps selected.

\*\* Customer incoming supply pressure to be less than 40 psi

NOTE: 30 gallon tank has single vent.

**Note: Optional Float Controls are available.  
Steam Tank Heaters are also available with PRV valves if required**